

IN THE CLAIMS

Please amend the claims as follows. Any additional differences between the previous state of the claims and the claims below are unintentional and in the nature of typographical errors.

1. (Cancelled).

2. (Currently Amended) The method of Claim ~~[[1]]~~ 7, wherein identifying the ~~one or more~~ model parameters further comprises:

~~identifying one or more pole candidates and one or more model candidates using the projection; and~~

selecting at least one of the one or more pole candidates and selecting at least one of the one or more model candidates as the model parameters.

3. (Currently Amended) The method of Claim ~~[[1]]~~ 7, wherein:

the upper triangular matrix has a plurality of values along one of the ~~[[first]]~~ diagonals of the upper triangular matrix, each value being greater than or equal to zero.

4. (Cancelled).

5. (Currently Amended) The method of Claim [[4]] 7, wherein:  
the diagonals divide the upper triangular matrix into upper, lower, left, and right sections;  
and  
the one or more first defined areas in the upper triangular matrix are located in the right  
section of the upper triangular matrix.

6. (Cancelled).

7. (Currently Amended) A method, comprising: ~~The method of Claim 6,~~  
receiving a projection associated with a first signal and a second signal, the second signal  
comprising a first portion associated with the first signal and a second portion not associated  
with the first signal, the projection comprising an upper triangular matrix, the projection at least  
partially isolating the first portion of the second signal from the second portion of the second  
signal;  
identifying model parameters using at least a portion of the projection; and  
generating and storing a model associated with the model parameters, the model  
associating the first signal and the first portion of the second signal;  
wherein identifying the model parameters comprises:  
identifying one or more pole candidates using one or more first defined areas in  
the upper triangular matrix, the model parameters comprising at least one of the one or more pole  
candidates; and  
identifying one or more model candidates using one or more second defined areas  
in the upper triangular matrix, the model parameters comprising at least one of the one or more  
model candidates;  
wherein each of the one or more second defined areas represents a matrix centered along  
one of [[the]] multiple diagonals of the upper triangular matrix.

8. (Previously Presented) The method of Claim 7, wherein:  
each matrix centered along one of the diagonals of the upper triangular matrix comprises a backward column Hankel matrix; and  
identifying the one or more model candidates comprises rewriting each backward column Hankel matrix as a forward column Hankel matrix.

9. (Currently Amended) The method of Claim ~~[[4]]~~ 7, wherein:  
~~defining the one or more areas in the upper triangular matrix comprises defining multiple areas in the upper triangular matrix; and~~  
identifying the ~~one or more~~ model parameters comprises identifying one or more model parameters for each of ~~[[the]]~~ multiple first defined areas in the upper triangular matrix.

10. (Currently Amended) The method of Claim 9, wherein:  
the one or more model parameters associated with different first defined areas in the upper triangular matrix are different; and  
identifying the ~~one or more~~ model parameters further comprises selecting the one or more model parameters associated with a specific one of the first defined areas in the upper triangular matrix.

11. (Currently Amended) A method, comprising: The method of Claim 10;  
wherein: the upper triangular matrix comprises a first upper triangular matrix; and  
receiving a projection associated with a first signal and a second signal, the second signal  
comprising a first portion associated with the first signal and a second portion not associated  
with the first signal, the projection comprising a first upper triangular matrix, the projection at  
least partially isolating the first portion of the second signal from the second portion of the  
second signal;  
identifying one or more model parameters using at least a portion of the projection; and  
generating and storing a model associated with the one or more model parameters, the  
model associating the first signal and the first portion of the second signal;  
wherein identifying the one or more model parameters comprises:  
identifying one or more model parameters for each of multiple defined areas in  
the first upper triangular matrix; and  
selecting the one or more model parameters associated with a specific one of the  
defined areas in the first upper triangular matrix; and  
wherein selecting the one or more model parameters associated with the specific one of  
the defined areas in the first upper triangular matrix comprises:  
for each defined area in the first upper triangular matrix, generating a matrix  
comprising a forward column Hankel matrix based on a prediction error, the prediction error  
associated with the one or more model parameters that are associated with that defined area;  
for each generated matrix, performing canonical QR-decomposition on the matrix

to form a second upper triangular matrix, each second upper triangular matrix having an upper right portion denoted  $R_{E3}$ ;

for each second upper triangular matrix, identifying a value for  $\|R_{E3}\|_2^2$ ; and

selecting the one or more model parameters associated with the defined area having the second upper triangular matrix with a smallest value for  $\|R_{E3}\|_2^2$ .

12. (Cancelled).

13. (Currently Amended) The apparatus of Claim ~~[[12]]~~ 17, wherein the at least one processor ~~is operable to identify~~ identifies the ~~one or more~~ model parameters by:

~~identifying one or more pole candidates and one or more model candidates using the projection; and~~

selecting at least one of the one or more pole candidates and selecting at least one of the one or more model candidates as the model parameters.

14. (Currently Amended) The apparatus of Claim ~~[[12]]~~ 17, wherein:

the upper triangular matrix has a plurality of values along one of the ~~[[first]]~~ diagonals of the upper triangular matrix, each value being greater than or equal to zero.

15.-16. (Cancelled).

17. (Currently Amended) An apparatus, comprising: The apparatus of Claim  
16, wherein:

at least one input receiving a first signal and a second signal, the second signal  
comprising a first portion associated with the first signal and a second portion not associated  
with the first signal; and

at least one processor:

generating a projection associated with the first and second signals and  
identifying model parameters using at least a portion of the projection, the projection comprising  
an upper triangular matrix, the projection at least partially isolating the first portion of the second  
signal from the second portion of the second signal; and

generating and storing a model associated with the model parameters, the model  
associating the first signal and the first portion of the second signal;

wherein the at least one processor identifies the model parameters by:

identifying one or more pole candidates using one or more first defined areas in  
the upper triangular matrix, the model parameters comprising at least one of the one or more pole  
candidates; and

identifying one or more model candidates using one or more second defined areas  
in the upper triangular matrix, the model parameters comprising at least one of the one or more  
model candidates; and

wherein each of the one or more second defined areas represents a matrix centered along  
one of [[the]] multiple diagonals of the upper triangular matrix. ;

~~each matrix centered along one of the diagonals of the upper triangular matrix comprises a backward column Hankel matrix; and~~

~~the at least one processor is operable to identify the one or more model candidates by rewriting each backward column Hankel matrix as a forward column Hankel matrix.~~

18. (Currently Amended) The apparatus of Claim ~~[[15]]~~ 17, wherein:

~~the at least one processor is operable to define the one or more areas in the upper triangular matrix by defining multiple areas in the upper triangular matrix; and~~

the at least one processor is ~~operable to identify~~ identifies the ~~one or more~~ model parameters by identifying one or more model parameters for each of ~~[[the]]~~ multiple first defined areas in the upper triangular matrix.



19. (Currently Amended) An apparatus, comprising: ~~The apparatus of Claim~~  
~~18, wherein: the one or more model parameters associated with different defined areas in the first~~  
~~upper triangular matrix are different; and~~

at least one input receiving a first signal and a second signal, the second signal  
comprising a first portion associated with the first signal and a second portion not associated  
with the first signal; and

at least one processor:

generating a projection associated with the first and second signals and  
identifying one or more model parameters using at least a portion of the projection, the  
projection comprising a first upper triangular matrix, the projection at least partially isolating the  
first portion of the second signal from the second portion of the second signal; and

generating and storing a model associated with the one or more model parameters,  
the model associating the first signal and the first portion of the second signal;

wherein the at least one processor identifies the one or more model parameters by:

identifying one or more model parameters for each of multiple defined areas in  
the first upper triangular matrix; and

selecting the one or more model parameters associated with a specific one of the  
defined areas in the first upper triangular matrix; and

wherein the at least one processor ~~is operable to select~~ the one or more model  
parameters associated with ~~[[a]]~~ the specific one of the defined areas in the first upper triangular  
matrix by:

for each defined area in the first upper triangular matrix, generating a matrix comprising a forward column Hankel matrix based on a prediction error, the prediction error associated with the one or more model parameters that are associated with that defined area;

for each generated matrix, performing canonical QR-decomposition on the matrix to form a second upper triangular matrix, each second upper triangular matrix having an upper right portion denoted  $R_{E3}$ ;

for each second upper triangular matrix, identifying a value for  $\|R_{E3}\|_2^2$ ; and

selecting the one or more model parameters associated with the defined area having the second upper triangular matrix with a smallest value for  $\|R_{E3}\|_2^2$ .

20. (Cancelled).

21. (Currently Amended) The computer program of Claim [[20]] 24, wherein the computer readable program code that identifies the ~~one or more~~ model parameters comprises:

~~computer readable program code that identifies one or more pole candidates and one or more model candidates using the projection; and~~

computer readable program code that selects at least one of the one or more pole candidates and that selects [[ing]] at least one of the one or more model candidates as the model parameters.

22. (Currently Amended) The computer program of Claim [[20]] 24, wherein: the upper triangular matrix has a plurality of values along one of the [[first]] diagonals of the upper triangular matrix, each value being greater than or equal to zero.

23. (Cancelled).

24. (Currently Amended) A computer program embodied on a computer readable medium, the computer program comprising: The computer program of Claim 23, wherein:

computer readable program code that receives a projection associated with a first signal and a second signal, the second signal comprising a first portion associated with the first signal and a second portion associated with at least one disturbance, the projection comprising an upper triangular matrix, the projection at least partially isolating the first portion of the second signal from the second portion of the second signal;

computer readable program code that identifies model parameters using at least a portion of the projection; and

computer readable program code that generates and stores a model associated with the model parameters, the model associating the first signal and the first portion of the second signal;

wherein the computer readable program code that identifies the model parameters comprises:

computer readable program code that identifies one or more pole candidates using one or more first defined areas in the upper triangular matrix, the model parameters comprising at least one of the one or more pole candidates; and

computer readable program code that identifies one or more model candidates using one or more second defined areas in the upper triangular matrix, the model parameters comprising at least one of the one or more model candidates; and

wherein each of the one or more second defined areas represents a matrix centered along

one of ~~[[the]]~~ multiple diagonals of the upper triangular matrix; ~~;~~

~~each matrix centered along one of the diagonals of the upper triangular matrix comprises a backward column Hankel matrix; and~~

~~the computer readable program code that identifies the one or more model candidates further comprises computer readable program code that rewrites each backward column Hankel matrix as a forward column Hankel matrix.~~

25. (Currently Amended) The computer program of Claim ~~[[23]]~~ 24, wherein:

~~the computer readable program code that defines the one or more first areas in the upper triangular matrix defines multiple first areas in the upper triangular matrix; and~~

the computer readable program code that identifies the one or more model parameters comprises computer readable program code that identifies one or more model parameters for each of ~~[[the]]~~ multiple first defined areas in the upper triangular matrix.

26. (Currently Amended) The computer program of Claim 25, wherein:  
~~the upper triangular matrix comprises a first upper triangular matrix;~~  
the one or more model parameters associated with different first defined areas in the  
[[first]] upper triangular matrix are different; and  
the computer readable program code that identifies the ~~one or more~~ model parameters  
further comprises computer readable program code that selects the one or more model  
parameters associated with a specific one of the first defined areas in the [[first]] upper triangular  
matrix.

27. (Currently Amended) A computer program embodied on a computer readable medium, the computer program comprising: The computer program of Claim 26,

computer readable program code that receives a projection associated with a first signal and a second signal, the second signal comprising a first portion associated with the first signal and a second portion associated with at least one disturbance, the projection comprising a first upper triangular matrix, the projection at least partially isolating the first portion of the second signal from the second portion of the second signal;

computer readable program code that identifies one or more model parameters using at least a portion of the projection; and

computer readable program code that generates and stores a model associated with the one or more model parameters, the model associating the first signal and the first portion of the second signal;

wherein the computer readable program code that identifies the one or more model parameters comprises:

computer readable program code that identifies one or more model parameters for each of multiple defined areas in the first upper triangular matrix; and

computer readable program code that selects the one or more model parameters associated with a specific one of the defined areas in the first upper triangular matrix; and

wherein the computer readable program code that selects the one or more model parameters associated with the specific one of the [[first]] defined areas comprises:

computer readable program code that, for each [[first]] defined area in the first

upper triangular matrix, generates a matrix comprising a forward column Hankel matrix based on a prediction error, the prediction error associated with the one or more model parameters that are associated with that [[first]] defined area;

computer readable program code that, for each generated matrix, performs canonical QR-decomposition on the matrix to form a second upper triangular matrix, each second upper triangular matrix having an upper right portion denoted  $R_{E3}$ ;

computer readable program code that, for each second upper triangular matrix, identifies a value for  $\|R_{E3}\|_2^2$ ; and

computer readable program code that selects the one or more model parameters associated with the [[first]] defined area having the second upper triangular matrix with a smallest value for  $\|R_{E3}\|_2^2$ .

28. (Currently Amended) The method of Claim [[1]] 7, wherein the projection at least partially isolates the first portion of the second signal from the second portion of the second signal in an orthogonal space.



29. (Currently Amended) The apparatus of Claim ~~[[12]]~~ 17, wherein the at least one processor ~~is further operable to use~~ the ~~one or more~~ model parameters associated with the stored model to de-noise the second signal.

30. (Currently Amended) The method of Claim ~~[[1]]~~ 7, wherein:  
[[the]] a first of the diagonals extends from [[the]] an upper left corner to a lower right corner of the upper triangular matrix; and  
[[the]] a second of the diagonals extends from [[the]] a lower left corner to an upper right corner of the upper triangular matrix.

31. (Currently Amended) The method of Claim ~~[[1]]~~ 7, further comprising:  
controlling at least a portion of a process using the model.

32. (New) The apparatus of Claim 17, wherein:  
each matrix centered along one of the diagonals of the upper triangular matrix comprises a backward column Hankel matrix; and  
the at least one processor identifies the one or more model candidates by rewriting each backward column Hankel matrix as a forward column Hankel matrix.

33. (New) The computer program of Claim 24, wherein:

each matrix centered along one of the diagonals of the upper triangular matrix comprises a backward column Hankel matrix; and

the computer readable program code that identifies the one or more model candidates further comprises computer readable program code that rewrites each backward column Hankel matrix as a forward column Hankel matrix